



# X BLUE TROLLEY

**BASIC****OPTIONAL:**upon request  
telescopic hose  
for tank**PRO**

FEATURES	12V DC	230V AC 50Hz	230V AC 60Hz	115V AC 60Hz
Voltage AC [V, Hz]:	12	230, 50	230, 60	115, 60
Current max [A]:	20	1,95	1,95	3,5
Power [W]:	200	350	350	350
Motor protection	IP55	IP55	IP55	IP55
On/Off switch	Yes	Yes	Yes	Yes
Cable [m]:	2	2	2	2
Duty cycle [min]:	S2 20	S2 20	S2 20	S2 20
Flow rate max [LPM / GPM]:	36 / 9,2	34 / 9	34 / 9	34 / 9
Pression Max [bar]:	1,9	1,5	1,5	1,5
Suction dry height [m]:	2	2	2	2
By-Pass valve:	Yes	Yes	Yes	Yes
Built in filter [ $\mu$ m]:	No	No	No	No
Motor holder:	Yes	Yes	Yes	Yes
Suction hose [material, $\varnothing$ , m]:	Rubber, 20, 3	Rubber, 20, 3	Rubber, 20, 3	Rubber, 20, 3
Delivery hose [material, $\varnothing$ , m]:	Rubber, 20, 3	Rubber, 20, 3	Rubber, 20, 3	Rubber, 20, 3
Nozzle:	Manual*/automatic**	Manual*/automatic**	Manual*/automatic**	Manual*/automatic**
IBC valve:	Included	Included	Included	Included
Telescopic hose for tank:	Upon request	Upon request	Upon request	Upon request
Flowmeter:	InLine**	InLine**	InLine**	InLine**
Seal material:	Viton	Viton	Viton	Viton
Temperature min/max [ $^{\circ}$ C]:	-5 / +40	-5 / +40	-5 / +40	-5 / +40
Allowed fluids:	AdBlue, AUS 32, Water	AdBlue, AUS 32, Water	AdBlue, AUS 32, Water	AdBlue, AUS 32, Water
Forbidden fluids:	Gas, Alcool, Gasoline, Diesel, Kerosene	Gas, Alcool, Gasoline, Diesel, Kerosene	Gas, Alcool, Gasoline, Diesel, Kerosene	Gas, Alcool, Gasoline, Diesel, Kerosene
Noise 1 m [dB]:	70	70	70	70
Net weight [Kg]:	33	33	33	33
Gross weight [Kg]:	35	35	35	35

**ACCESSORIES:** automatic nozzle on request

\*Basic version \*\*Pro version